

Data Sheet 21.2

Two-way Valves Type Q-16



Two-way valves

Two-way valves type LM and LN can be used for diverting the grain flow.

Type LM valves are used where a vertical spout divides into two sloping spouts while type LN delivers the grain in a sloping and a vertical spout.

For manual operation of the two-way valves a handle/lever is used, this can be mounted on the side of the valve in the position that is most convenient for the particular location. The actual position of the shutter is shown by means of an arrow pointing in the direction of the grain flow.

This device can be replaced by an electrical indicator showing flow direction by means of signal lights which, if required can be fitted after installation. Manually operated two-way valves type LN can be supplied with shutter regulation on either the left or right hand side.

Additionally the two-way valves can be delivered pneumatically operated enabling a number of valves to be easily controlled from a remote control panel.

Manually	Manually w. indication	Pneumatically	Motorised w. indication
LM32	LM34	LM38	LM39

Manually	Manually w. indication	Pneumatically	Motorised w. indication
LM352	LM354	LM355	LM359

Shown as LN33

Manually right	Manually w. indication - right	Pneumatically	Motorised w. indication
LN32	LN34	LN38	LN39
Manually left	Manually w. indication - left		
LN33	LN35		

Manually	Manually w. indication	Pneumatically
LN352	LN354	LN355

The shown handles have to be ordered separately.

Copyright © - The right to alterations is reserved

